

Everlac Wood Preserver

Technical
Data Sheet
Number 9

Everlac Wood Preserver brings out the true beauty of timber, whilst also penetrating to give a long lasting protection against water absorption, dry rot, mildew, woodworm and moulds

PURPOSE

Everlac Wood Preserver can be used on a number of substrates such as weatherboards, fencing, wooden garages, garden sheds, interior panelling, and skirting boards.

METHOD OF APPLICATION

Exterior

Do not apply to wet surfaces. Remove surface debris.

Everlac Wood Preserver may be applied by brush, roller or spray (Graco President or gravity fed)

Apply a minimum of two coats, the first to act as a base coat and the second as a finishing top coat.

Further coats may be applied to achieve the desired depth of colour.

Interior

Everlac Wood Preserver may be applied by brush, roller or spray (Graco President or gravity fed)

Everlac Wood Preserver can be applied as a single coat, however further coats may be applied to achieve the desired depth of colour.

SPECIAL PROPERTIES

- Will not crack, blister or lose colour
- Algae and fungi resistant
- Long life
- Easy to apply

TECHNICAL DATA

COVERAGE - Coverage will vary depending on the porosity of the substrate but will be typically 5m²/litre per coat.

DRYING AND CURING – Touch dry 12-24 hours, hardens fully over 4 weeks. Colour darkens over this period.

Do not apply if rain is imminent. Rain will affect the appearance of the coating if not touch dry.

Apply above 5°C and rising.

COLOUR - Dark Oak, Light Oak, Mahogany

STORAGE – Frost free environment, out of direct sunlight.

SHELF LIFE – 12 months unopened.

CLEANING EQUIPMENT - All tools and equipment should be cleaned immediately after use with white spirits. Wipe up spots or splatters before they dry.

PACKAGING - 5 and 25 litre metal cans.

FLASHPOINT - 38°C

HEALTH & SAFETY – Wood preserver is hazardous and flammable. Strict safety regulations should be adhered to. Goggles and gloves to be worn at all times. Use air fed mask when spraying.

A Material Safety Data Sheet is available on request.