

# Everlac Flexible Filler

Technical  
Data Sheet  
Number 24

**Everlac Flexible Filler** is formulated to act as a multi purpose material for the filling of cracks, indentations and joints in masonry and wood panelling as well as acting as an adhesive for the fixing of ceramic tiles.

## PURPOSE

**Everlac Flexible Filler** is formulated to act as a multi purpose material for the filling of cracks, indentations and joints in masonry and wood panelling, in particular prior to **Everlac's** range of exterior wall coatings and wood finishes. **Everlac Flexible Filler** also acts as an adhesive for the fixing of ceramic tiles.

## METHOD OF APPLICATION

When applying **Everlac Flexible Filler** into cracks on masonry these should first be prepared by removing any loose paint or render to the surrounding area.

Fine cracks should be chiselled or vied out to a minimum width of 5mm prior to filling.

**Everlac Flexible Filler** should be applied to a thickness of no more than 5mm in any one application. Where the thickness of repair is greater than 5mm, application should be carried out in stages and sufficient time allowed between coats to allow for drying.

**Everlac Flexible Filler** may be applied by either trowel or spatula or ceramic tile comb when used as a tile adhesive.

Once dry, **Everlac Flexible Filler** may be sanded down using any traditional sanding methods and materials.

**Everlac Flexible Filler** is designed to act as a surface preparation and must therefore be topcoated when dry.

## SPECIAL PROPERTIES

- Water based
- Read mixed
- Easily sanded once dry
- Flexible
- Excellent substrate adhesion

## TECHNICAL DATA

**COVERAGE** – 1.35kg/m<sup>2</sup>

**COLOUR AND APPEARANCE** – White and slightly textured (when left un-sanded)

**FOR APPLICATION AS A TILE ADHESIVE** – Conforms to BS 5980: 1980 TYPE 2 CLASS AA. For use in kitchens, bathrooms and domestic showers

**STORAGE** - Always store above 5°C.

**SHELF LIFE** - 12 months in original sealed packs in dry conditions.

**CLEANING EQUIPMENT** - All tools and equipment should be cleaned immediately after use with water.

**PACKAGING** - 15kg Packs.

**FLASHPOINT** - None, water based.

**HEALTH & SAFETY** - **Everlac Flexible Filler** is non flammable with no measurable flash point.

A Material Safety Data Sheet is available on request.